

## INTERFATA CAN/FMS

Compatibilitate cu interfata FMS implementata de fabricantii: MAN, Mercedes-Benz, SCANIA, Renault-Trucks, ERF, VOLVO, DAF, IVECO

### CONFORMITATE RoHS

### AM CONSULTING SERV SRL

Fax: 021 490 43 66

Tel: 0733 938 978

Email: amcs@amcs.ro

www.amcs.ro



CAN 2.0A si 2.0B;  
Compatibil cu standardul SAE J1939;  
Interfata RS232;  
Dimensiuni: 50 x 36 x 20mm;  
Greutate : 20g ;  
Alimentare : 7 – 35 VDC  
Temp. Operare : -35 - +85 grade C

Adaptorul CAN/FMS permite extragerea de informatii de pe bus-ul CAN, informatii care sunt furnizate in format ASCII printr-o interfata RS232. Configurarea se face prin comenzi AT.

Parametrii extrasi :

- Vehicle speed;
- Cruise control status;
- Clutch switch;
- PTO status;
- Accelerator pedal position;
- Total fuel used;
- Fuel level;
- Engine speed (rpm);
- Truck axle weight;
- Total engine hours;
- Vehicle identification number;
- Next regular maintenance;
- Tacho information;
- Tachograf vehicle speed;
- Brake switch.