

GT864 QUAD Terminal

The GSM/GPRS Quad Band Modem with TCP/IP stack, SMTP, E-mail, SMS and CSD

Features:

- Quad Band
- RS232 serial port
- GPRS Class 10
- TCP/IP stack
- SMS and CSD
- E-mail
- Audio interface
- 5-36V DC supply
- -30°C to +75°C
- CE approval
- FCC approval
- E-Marking
- RoHS compliant
- 3 Status LEDs
- SIM card holder
- I/O variants available
- Serial port multiplexer
- Made in Germany



GT864 QUAD Terminal

The GT864 QUAD Terminal is a self contained unit featuring the latest GSM/GPRS technology from Telit.

GT864 QUAD Terminal is an excellent product for system integrators whose focus is on application development using a ready to start modem with standard connectors.

The audio interface handles voice calls and offers connectivity with a head set.

Benefits

- Quad Band functionality allows operation on all GSM-frequencies.
- The RS232 port allows connectivity to all relevant PC's and control boards in office and industrial environments.
- The GPRS class 10 allows fast data transfer on up to four simultaneous GPRS-downlink channels and up to two uplink channels.
- The included TCP/IP stack gives system integrators fast access to IP connections and supports E-mail services just by using AT commands.
- The robust connectors and the professional housing allow the integration in tough environments such as vending machines, alarm systems or any other telemetry application.
- The extended temperature range from -30°C up to +75°C enables for integration in harsh environments.
- The wide input voltage range of up to 36V and the E-Marking allow the integration in vehicle applications for telematic solutions.

GT864 QUAD Terminal, the GSM/GPRS Quad Band Modem

Product Features

- Quad Band GSM/GPRS
- GSM 850/900 Power class 4 (33dBm)
- GSM 1800/1900 Power class 1 (30dBm)
- Mobile Class B
- Extended Measurement Reporting
- Compliant with 3GPP Release 99 Protocol Stack
- Power supply: 5 36 VDC
- Overall dimensions (excluding connectors):
- 77 x 67 x 26 mm
- Temperature range:
- -30°C to +75°C (Operational)
- -40°C to +85°C (Storage temperature)
- Weight: ~ 100g

Interfaces

- RS232 9pin DSub
- Audio Microphone / Loudspeaker (USB mini connector)
- Power: 5 - 36VDC (RJ11)
- Antenna: 50 Ohm (FME male)
- SIM card reader: 1,8V/3V interface with SIM detection
- Control by AT commands (GSM 27.005, 27.007 plus proprietary commands)

Data Features

- GPRS Class 10
- Multiple simultaneous PDP contexts
- GPRS Coding Schemes CS1-CS4
- Transparent and non-transparent CSD up to 9.6 kbps
- Modem Type; V21, V22, V23, V22bis, V26ter, V32, V34, V24
- V42bis compression
- GSM supplementary services supported
- GSM 27.010 Multiplexing Protocol
- USSD
- Fax Group 3, Class1

Firmware Update Over the Air

Firmware update over the air based on Telit Service TFUS; only the delta will be sent via GPRS; GT864 has to be pre-registered to the database

CEP

CEP AG
Raiffeisenallee 12b
D-82041 Oberhaching/Germany
Phone: +49 89 450 292 - 0
Fax: +49 89 450 292 - 22
Internet: www.cepag.de
Mail: info@cepag.de V1-3 Feb. 2009

Short Message Service Features (SMS)

- Text and PDU mode
- Point to Point mobile originated and mobile terminated SMS (MT/MO)
- SMS Cell Broadcast

Internet Protocol

- TCP/IP protocol stack
- Extensive AT Command access to TCP/IP stack
- Multiple sockets with listening/server capability
- IPv4 protocol
- Dynamic & Static IP address allocation
- PPP protocol (PAP)
- UDP protocol
- FTP client File Transfer Protocol (file transfers)
- SMTP
- E-mail

Audio

- Telephony, Emergency Calls
- HR, FR, EFR, AMR (Half Rate, Full Rate, Enhanced Full Rate and Multi Rate voice codec's)
- Superior Echo Cancellation /& Noise Reduction
- DTMF

Other Features

- SIM Application Toolkit Class 2
- 3 x LED for status indication
- Power Supply voltage measurement via AT-Command
- SIM Phonebook
- Fixed Dialling Number (FDN)
- Real Time Clock
- IRA character set
- Jamming Detection & report
- I/O variant with 4 digital inputs, 1 analogue input, 1 digital output and Python programming capability available (GT864 PY Terminal)

Accessories

- CEP Power Supply for GSM/GPRS Terminals
- Antennas
- Head Sets
- Cables for power, audio and RS232

Authorised distributor of

 **Telit** wireless solutions

Note: Specification is preliminary and subject to change without prior notice.