

# SKYTRACK Picotrack

Solutii de monitorizare miniaturale



## SKYTRACK

Cel mai mic echipament de localizare cu buton de urgenta

CONFORMITATE RoHS

Fabricat in Germania

AM CONSULTING SERV SRL

Fax: 021 490 43 66  
Tel: 0733 938 978  
Email: amcs@amcs.ro  
www.amcs.ro



Dimensiuni : 43 x 34 x 11 mm;  
Greutate : 22 g  
Consum extrem de redus;  
GSM/GPRS quad band;  
Receptor GPS ultraperformant (inclusiv unele cladiri);  
Acumulator intern litiu – polimer;

Procesor performant care permite stocarea de pozitii precum si definirea unor zone geografice de restrictii;

Toate antenele integrate ;

Senzor de miscare incorporat care permite extinderea functionarii autonome ;

Optional: Accelerometru intern 3D ultrasensibil care permite detectarea miscarii si directia de deplasare , inclusiv pe verticala; acceleratii masurate : max  $\pm 8g$ ;

Optional: Senzor optic (exemplu : permite sesizarea deschiderii unui container);

Temperaturi de operare :  $-35 \div +85 \text{ }^{\circ}\text{C}$

**Picotrack “ Power”** – versiune prevazuta cu acumulator de capacitate dubla

Timpi functionare pe acumulatorul propriu :

- 6 saptamani cu pozitii la fiecare 4 ore ;
- 24 ore de functionare continua cu pozitii la fiecare 5 min

**Picotrack “ Listen-In ”** – versiune prevazuta cu microfon



Picotrack „power“



**Picotrack “Flex”** – versiune flexibila destinata monitorizarii teancurilor de bancnote

Dimensiuni : 105 x 52 x 7 mm;  
Microfon incorporat ;

Senzor miscare incorporat ;

Toate antenele incluse ;

Acumulator intern litiu-polimer

Timp functionare : 3 saptamani cu pozitii la 4 ore