

Antenna SMA Connector Status LED SIM Card Holder



Introduction

QSM-26 is a DIN rail mounted GSM/GPRS modem. The unit has a built in Quad Band (850/900/1800/1900MHz) Wavecom Q2686 modem, 2 digital inputs, 2 power relay outputs and a serial RS-232 port. Inputs and outputs function as typical general purpose I/O (GPIO).

Technical characteristics

Power supply	12/24 VDC, 8mA to 0.2A max (all DO on)
Wireless modem	Wavecom Q2686
Radio Bands	Quad Band 850/900/1800/1900 MHz
Bearers	GSM + GPRS class 10
Approvals	R&TTE, CE, GCF, FCC, PTCRB, China RTE, AT&T
Digital inputs	2, 12..30VDC
Digital outputs	2, relay 250V/10A (AC1)
Serial interface	RS232C, up to 921 kBit/s
Dimensions:	75 x 90 x 58 mm

Accessories

RPS-1210: 220V/12VDC, 0.8A power supply unit
Quad Band GSM Antenna

Ordering information

QSM-26-xx

xx=12: 12 VDC power supply

xx=24: 24 VDC power supply

RoHS Compliant
Directive 2002/95/EC



Infinite Informatics, Ltd.
1, Valaoritou Street
GR-54626 Thessaloniki, Greece
Phone: +30-2310-553545, Fax: +30-2310-552006
Email: sales@indinf.gr
URL: www.infinite.com.gr, www.indinf.gr

Representative - authorized dealer

Wireless MODEM QSM-26